

MG-VRT-AH

THERMAL TRANSFER SYSTEM FOR SHEET MEDIA

Panel plates self adhesive with holes

customisable

MG-VRT-AH rigid PVC self adhesive panel plates are used to create name plates, rating plates, data plates using company logos, technical data, serial numbers, EC certification, etc. Transparent polycarbonate covers can be used for increased durability.

Consult us for availability of other colours.

Note: UV resistance may vary between colours.



Material: Rigid PVC, self extinguishing class V0: UL94; the colours white PVC10050WH and yellow PVC10050YE are UL approved.

Operating temperature range: -30°C (-22°F) to +60°C (+140°F)

Application temperature range: +10°C (+50°F) to +40°C (+104°F)



Size mm	Type						No. Holes	Tags per sheet	Quantity	SW code
	white PVC10050WH	yellow PVC10050YE	grey	red	blue	black				
15 x 52	88940					88140	2	14	350	831
20 x 40	88920	88420	88720GY				2	10	250	864
25 x 50	88906	88406					2	8	200	860
25 x 75	88907	88407		88207			2	4	100	809
25 x 80	88942					88142	2	4	100	832
25 x 100	88914	88414		88214			2	4	100	206
35 x 50	88941					88141	2	6	150	833
35 x 75	88929						2	3	75	817
35 x 85	88944	88444					2	3	75	823
35 x 100	88909	88409					2	3	75	818
35 x 100	88910	88410					4	3	75	818
42 x 78	88922	88422					2	2	50	819
50 x 100	88911	88411		88211			4	2	50	811
75 x 120	88915	88415				88115	4	1	25	816
105 x 110	88912	88412	88712GY				4	1	25	859
25 x 140	88927	88427					2	4	100	871
29 x 140	88943					88143	2	3	75	834
30 x 115	88967	88467					2	3	75	780
35 x 142	88939						2	3	75	835
40 x 150	88968	88468					2	2	50	781
50 x 140	88919				88619		4	2	50	872
50 x 150	88956						4	2	50	843
82 x 142	88938						4	1	25	836
102 x 138				88237	88637		4	1	25	208



Directly on suitable surfaces.

template with PET support.....page 10
ribbons.....page 11