

MG-SIGNS

THERMAL TRANSFER SYSTEM FOR SHEET MEDIA

Panel legends

precut

The MG-SIGNS legends is used for in-house production of warning, hazard, prohibition and mandatory signs from pictograms provided in the library of GENIUSPRO software.

A highly versatile system for rapidly and accurately producing signs in all languages, on a one-off basis if required.



Material: Rigid PVC, self extinguishing class V0: UL94; the colours white PVC10050WH and yellow PVC10050YE are UL approved.

Operating temperature range: -30°C (-22°F) to +60°C (+140°F)

Application temperature range: +10°C (+50°F) to +40°C (+104°F)



Family	Shape	Self adhesive	Size mm	Type			Ø mm Holes	Tags per sheet	Quantity	SW code	
				white PVC10050WH	yellow PVC10050YE	red					
MG-SIGNS-R			40		990984			4	200	243	
			37 x 74		990713	990987		2	100	271	
			52 x 105		990714			2	100	272	
			Ø 62		990743			22,5	2	50	252
			Ø 62		990930			30	2	50	265
			Ø 90		990744			22,5	1	50	263
			Ø 90		990745			30,5	1	50	264
MG-SIGNS-A		✓	100		990704			1	50	262	
		✓	Ø 40	990927	990928	990858		4	200	250	
		✓	Ø 100	990705				1	50	253	
		✓	37 x 74		990711	990986		2	100	271	
		✓	40 x 80		990985			3	75	274	
	✓	52 x 105		990712			2	100	272		



i Directly on suitable surfaces.

template with PET support..... page 10
ribbons..... page 11