



# CONSOLE BOX

## FEATURES

- ✓ Up to Seven Single-Axis, Bi-directional Stepless Levers
- ✓ Up to Four Single/Dual Axis Stepped or Stepless Joysticks
- ✓ Options for Toggles, Potentiometers, Pushbuttons, and Rotary Switches for AUX functions
- ✓ Standard Four System Status/Diagnostic LEDs
- ✓ Unsurpassed Durability and Environmental Sealing
- ✓ Shoulder Harness Standard, Optional Belt Mounting
- ✓ Operates Using Two C-Cell Batteries
- ✓ Optional 8-Character LED Display
- ✓ 900MHz Direct Sequence Spread Spectrum (DSSS) Technology
- ✓ Push/Pull Stop Switch
- ✓ TILT Switch Field Enable/Disable
- ✓ On/Off Key Switch for Security



## SPECIFICATIONS

CONSOLE BOX	
POWER	
Operating Voltage	1.9 to 3.2VDC
Batteries	Two (2) C-Type Alkaline (typical)
Low V Warning	2.1V
Auto-Shutdown	2.0V
Inactivity Shutdown	Four Minutes Standard (Programmable)
ENVIRONMENT	
Operating Temp	-20°C to 55°C (-4°F to 131°F)
Storage Temp	-20°C to 85°C (-4°F to 185°F)
Humidity	0-95% non-condensing
LED INDICATORS	
TX/RX	Transmit Receive
BATT	Battery Life
A	A Selection
B	B Selection
ENCLOSURE	
Dimensions	10.4" x 5.6" x 5.5" 263.5mm x 131.5mm x 139mm
Total Weight	3.95 lbs. (1.8kg)
Material	Glass-Filled Nylon
Faceplate	Aluminum or Acrylic
RADIO	
Frequency	904-926MHz, 100mW, 450MHz, FCC Part 90 option
License	FCC Part 15, License Free
Modulation	Channel Hopping DSSS

